



How to change spark
plugs on **Toyota Auris**
E15 – replacement guide

VIDEO TUTORIAL




Important!

This replacement procedure can be used for:

TOYOTA Urban Cruiser (_P1_) 1.33 (NSP110_), TOYOTA Verso S (_P12_) 1.33 (NSP120_), TOYOTA Yaris Hatchback (_P9_) 1.33 VVT-i (NSP90_), TOYOTA PRIUS PLUS (ZVW4_) 1.8 Hybrid (ZVW4_), TOYOTA Yaris Hatchback (_P13_) 1.3 (NSP130_), TOYOTA AURIS (NRE15_, ZZE15_, ADE15_, ZRE15_, NDE15_) 1.6 (ZRE151_), TOYOTA Yaris Hatchback (_P9_) 1.8 VVTi (ZSP90_), TOYOTA COROLLA Saloon (E15_) 1.6 Dual VVTi (ZRE141), TOYOTA AVENSIS Saloon (ZRT27, ADT27) 1.6 (ZRT270_), TOYOTA AVENSIS Saloon (ZRT27, ADT27) 1.8 (ZRT271_), TOYOTA AVENSIS Saloon (ZRT27, ADT27) 2.0 (ZRT272_), TOYOTA AVENSIS Estate (ZRT27, ADT27) 1.6 (ZRT270_), TOYOTA AVENSIS Estate (ZRT27, ADT27) 1.8 (ZRT271_), TOYOTA AVENSIS Estate (ZRT27, ADT27) 2.0 (ZRT272_), TOYOTA AURIS (NRE15_, ZZE15_, ADE15_, ZRE15_, NDE15_) 1.33 Dual-VVTi (NRE150_), (+ 26)

The steps may slightly vary depending on the car design.

REPLACEMENT: SPARK PLUGS – TOYOTA AURIS E15. TOOLS YOU'LL NEED:



- Electronic spray
- High-temperature anti-seize lubricant
- Drive socket # 10
- Spark plug socket # 16
- Ratchet wrench
- Torque wrench
- Fender cover

BUY TOOLS


Replacement: spark plugs – Toyota Auris E15. Professionals recommend:

- The replacement procedure is the same for all spark plugs.
- Please note: all work on the car – Toyota Auris E15 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Open the bonnet.



2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.




3


Remove the engine cover.




- 4 Unplug the connectors from the ignition coils.




- 5 Clean the ignition coils.



- 6 Unscrew the fasteners of the ignition coils. Use a drive socket #10. Use a ratchet wrench.



- 7 Take out the ignition coils from the spark plug wells.




Replacement: spark plugs – Toyota Auris E15. AUTODOC recommends:


- Remember the sequence of steps for ignition coil demounting.

8 Clean dirt, dust and debris from inside the spark plug wells.


9 Unscrew the spark plugs. Use the spark plug socket #16. Use a ratchet wrench.




10 Take out the spark plugs.



11 Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs.



12 Install the new spark plugs into their mounting seats. Use the spark plug socket #16.



- 13 Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 20 nm torque.



Replacement: spark plugs – Toyota Auris E15. AUTODOC experts recommend:

- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.

- 14 Treat the ignition coil tips. Use high-temperature grease.

- 15 Install the ignition coils to the spark plug wells. Make sure you hear a click indicating that it is locked in place.




AUTODOC recommends:

- Replacement: spark plugs – Toyota Auris E15. Follow the installation steps.


16

Tighten the fasteners of the ignition coils. Use a drive socket #10. Use a ratchet wrench.




17

Treat the ignition coil connector with electronic spray. The spray will protect the electrical contacts from corrosion, oxidation, and will reduce the contact resistance.




18

Plug in the connectors of the ignition coils.



19

Install the engine cover and secure it.



AUTODOC recommends:

- Make sure the engine cover is properly seated. It should not be displaced with respect to the guiding fasteners.
- Replacement: spark plugs – Toyota Auris E15. Do not use excessive force during installation. This may damage the fasteners.


20 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

21 Shut off the engine.

22 Remove the fender protection cover.



23 Close the hood.



WELL DONE!

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR TOYOTA

SPARK PLUGS: A WIDE SELECTION

CHOOSE CAR PARTS FOR TOYOTA AURIS E15

SPARK PLUGS FOR TOYOTA: BUY NOW

SPARK PLUGS FOR TOYOTA AURIS E15: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.